

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Adhesive 498 20-X (4010)**  
Revision date : 21.06.2016 Version (Revision) : 4.0.0 (3.0.0)  
Print date : 19.07.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Lascaux Acrylic Adhesive 498 20-X (4010)

**1.2 Relevant identified uses of the substance or mixture and uses advised against**  
**Relevant identified uses**

Adhesives for the preservation and restoration of art and cultural assets

**1.3 Details of the supplier of the safety data sheet**

**Supplier (manufacturer/importer/only representative/downstream user/distributor)**

Lascaux Colours & Restauro  
Barbara Diethelm AG

**Street :** Zürichstrasse 42

**Postal code/city :** 8306 Brüttisellen

**Telephone :** +41 44 807 41 41

**Telefax :** +41 44 807 41 40

**Information contact :** techsupport@lascaux.ch

**1.4 Emergency telephone number**

Tox Info Suisse  
24-h-emergency number 145  
Tel. +41 44 251 51 51 (international)

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

**2.2 Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



Flame (GHS02) · Exclamation mark (GHS07)

**Signal word**

Warning

**Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves/protective clothing.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Adhesive 498 20-X (4010)**  
Revision date : 21.06.2016 Version (Revision) : 4.0.0 (3.0.0)  
Print date : 19.07.2016

P332+P313 If skin irritation occurs: Get medical advice/attention.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

#### Special rules for supplemental label elements for certain mixtures

EUH208 Contains 2-METHYL-2H-ISOTHIAZOL-3-ONE ; 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.

### 2.3 Other hazards

None

## SECTION 3: Composition / information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

XYLENE ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction :  $\geq 15 - < 20$  %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315

AMMONIA, ANHYDROUS ; EC No. : 231-635-3; CAS No. : 7664-41-7

Weight fraction :  $< 0,5$  %

Classification 1272/2008 [CLP] : Flam. Gas 2 ; H221 Acute Tox. 3 ; H331 Skin Corr. 1B ; H314 Aquatic Acute 1 ; H400

#### Additional information

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

#### Following inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration. Unconsciousness: lateral position - call a physician.

#### In case of skin contact

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

#### After ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Adhesive 498 20-X (4010)**  
Revision date : 21.06.2016 Version (Revision) : 4.0.0 (3.0.0)  
Print date : 19.07.2016

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray.

## Unsuitable extinguishing media

Waterjet.

### 5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

### 5.3 Advice for firefighters

#### Special protective equipment for firefighters

Appropriate breathing apparatus may be required.

### 5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

### 6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

### 6.4 Reference to other sections

None

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid contact with skin and eyes. Do not inhale the vapour. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws. For personal protection see Section 8. Gas mask in case of spray processing.

#### Protective measures

##### Measures to prevent fire

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type.

#### Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class ( D ) : 3

Storage class (TRGS 510) ( D ) : 3

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Adhesive 498 20-X (4010)**  
Revision date : 21.06.2016 Version (Revision) : 4.0.0 (3.0.0)  
Print date : 19.07.2016

## Further information on storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from ignition sources - No smoking. Keep containers dry and cool. Keep containers in a well-ventilated place. Comply with the health and safety at work laws.

## 7.3 Specific end use(s)

None

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : MAK ( CH )

Limit value : 100 ppm / 435 mg/m<sup>3</sup>

Remark : H OL# B

Version : 01.01.2013

Limit value type (country of origin) : STEL ( CH )

Limit value : 200 ppm / 870 mg/m<sup>3</sup>

Remark : H OL# B

Version : 01.01.2013

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 100 ppm / 440 mg/m<sup>3</sup>

Peak limitation : 2(II)

Remark : H

Version : 02.04.2014

Limit value type (country of origin) : TRGS 903 ( D )

Parameter : Xylene / Whole blood (B) / End of exposure or end of shift

Limit value : 1,5 mg/l

Version : 31.03.2004

Limit value type (country of origin) : TRGS 903 ( D )

Parameter : Methylhippuric acid / Urine (U) / End of exposure or end of shift

Limit value : 2 g/l

Version : 31.03.2004

Limit value type (country of origin) : STEL ( EC )

Limit value : 100 ppm / 442 mg/m<sup>3</sup>

Remark : H

Version : 08.06.2000

Limit value type (country of origin) : TWA ( EC )

Limit value : 50 ppm / 221 mg/m<sup>3</sup>

Remark : H

Version : 08.06.2000

AMMONIA, ANHYDROUS ; CAS No. : 7664-41-7

Limit value type (country of origin) : MAK ( CH )

Limit value : 20 ppm / 14 mg/m<sup>3</sup>

Remark : SSC

Version : 01.01.2013

Limit value type (country of origin) : STEL ( CH )

Limit value : 40 ppm / 28 mg/m<sup>3</sup>

Remark : SSC

Version : 01.01.2013

Limit value type (country of origin) : TRGS 900 ( D )

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Adhesive 498 20-X (4010)**  
Revision date : 21.06.2016 Version (Revision) : 4.0.0 (3.0.0)  
Print date : 19.07.2016

Limit value : 20 ppm / 14 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 02.04.2014  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 50 ppm / 36 mg/m<sup>3</sup>  
Version : 08.06.2000  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 20 ppm / 14 mg/m<sup>3</sup>  
Version : 08.06.2000

## 8.2 Exposure controls

### Personal protection equipment

#### Eye/face protection

Use safety glasses.

#### Skin protection

##### Hand protection

Solvent-resistant protective gloves must be worn. For prolonged or repeated handling, use barrier creams to protect the exposed areas of the skin.

##### Body protection

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact. After skin contact wash thoroughly with soap and water or use recognised skin cleanser. Do Not use solvents or thinners.

#### Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn.

### Occupational exposure controls

#### Technical measures to prevent exposure

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit) , suitable respiratory protection must be worn.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state : Pasty.

Colour : White.

#### Odour

Poor, characteristic.

#### Safety relevant basis data

Initial boiling point and boiling range :	( 1013 hPa )	ca.	100 °C
Flash point :		ca.	25 °C
Vapour pressure :	( 50 °C )	ca.	30 hPa
Density :	( 20 °C )	ca.	1,0 g/cm <sup>3</sup>
pH :		ca.	9,0
Viscosity :	( 20 °C )		10000 - 20000 mPa.s

### 9.2 Other information

None

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Adhesive 498 20-X (4010)**  
Revision date : 21.06.2016 Version (Revision) : 4.0.0 (3.0.0)  
Print date : 19.07.2016

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No information available.

**10.2 Chemical stability**

No information available.

**10.3 Possibility of hazardous reactions**

No information available.

**10.4 Conditions to avoid**

Stable under recommended storage and handling conditions(See section 7).

**10.5 Incompatible materials**

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.6 Hazardous decomposition products**

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

No information available.

**11.4 Other adverse effects**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

**SECTION 12: Ecological information**

**12.1 Toxicity**

No information available.

**12.2 Persistence and degradability**

No information available.

**12.3 Bioaccumulative potential**

No information available.

**12.4 Mobility in soil**

No information available.

**12.5 Results of PBT and vPvB assessment**

No information available.

**12.6 Other adverse effects**

No information available.

**12.7 Additional ecotoxicological information**

There are no data available on the product itself. Do not empty into waters or drains.

**SECTION 13: Disposal considerations**

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Adhesive 498 20-X (4010)**  
Revision date : 21.06.2016 Version (Revision) : 4.0.0 (3.0.0)  
Print date : 19.07.2016

plant. Uncleaned packaging must be disposed of in the same manner as the medium.

## 13.1 Waste treatment methods

### Product/Packaging disposal

#### Waste codes/waste designations according to EWC/AVV

08 01 11: waste paint and varnish containing organic solvents or other dangerous substances.

## SECTION 14: Transport information

### 14.1 UN number

UN 1133

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

ADHESIVES

#### Sea transport (IMDG)

ADHESIVES

#### Air transport (ICAO-TI / IATA-DGR)

ADHESIVES

### 14.3 Transport hazard class(es)

#### Land transport (ADR/RID)

Class(es) : 3  
Classification code : F1  
Hazard identification number (Kemler No.) : 30  
Tunnel restriction code : D/E  
Special provisions : 640E · LQ 5 I · E 1 · Transport in containers with max. 450 litres contents are not subject to the regulations of ADR/RID.  
Hazard label(s) : 3

#### Sea transport (IMDG)

Class(es) : 3  
EmS-No. : F-E / S-D  
Special provisions : LQ 5 I · E 1 · IMDG 2.3.2.5 (<= 30 l)  
Hazard label(s) : 3

#### Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3  
Special provisions : E 1  
Hazard label(s) : 3

### 14.4 Packing group

III

### 14.5 Environmental hazards

Land transport (ADR/RID) : No

Sea transport (IMDG) : No

Air transport (ICAO-TI / IATA-DGR) : No

### 14.6 Special precautions for user

None

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Lascaux Acrylic Adhesive 498 20-X (4010)  
**Revision date :** 21.06.2016 **Version (Revision) :** 4.0.0 (3.0.0)  
**Print date :** 19.07.2016

**National regulations**

**Technische Anleitung Luft (TA-Luft) ( D ) :**

Weight fraction (Number 5.2.4. III) : < 1 %

**Water hazard class (WGK)**

Class ( D ) : 2 (Hazardous to water) Classification according to VwVwS

**15.2 Chemical Safety Assessment**

No information available.

**SECTION 16: Other information**

**16.1 Indication of changes**

None

**16.2 Abbreviations and acronyms**

None

**16.3 Key literature references and sources for data**

None

**16.4 Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]**

No information available.

**16.5 Relevant H- and EUH-phrases (Number and full text)**

H221	Flammable gas.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.

**16.6 Training advice**

None

**16.7 Additional information**

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.